

metalfire

| architectural fireplaces |

model URBAN MF 800-75 G T

Dimensions (mm)

- combustion chamber WxDxH 800 x 600 x 750
- length of burner 500
- external WxDxH 1066 x 600 x 2025
- fresh air 1 x Ø150

Technical Data (city gas)

for other types of gas see 'gasburner specifications' (options)

- appliance type B11AS/B14AS
- load 7,55 kW
- type of gas/pressure G20/20,25/25mBar
- gascat. I2E+, I2H, I2E, I2L
- weight +/- 132kg

Protection

- 'oxy-pilot'-protection
- ionization-protected pilot-flame
- secured flue pipe discharge
- secured oxygen supply


Specifications

- control unit on the right
- finishing: heat-resistant black paint
- lockable valve for fresh air and smoke gases
- grey pebbles
- remote control with electronic ignition
- one side closed with fixed glass panel
- one side with glass panel H=250mm (Ø200mm)

Options

- chimney fan RSVG 250
- sides combustion chamber finishing:
 - ribbed cast-iron
 - ceramic woodlogs
 - convection jacket (see options)

* valve for flue gases Ø200 or Ø250 depending on situation, for further info contact the Metalfire dealer



scale 1:20

www.metalfire.eu

EN 509 CE

General dimensional tolerances up to 6mm
Metalfire preserves the right to modify specifications without previous notice